

SINOTRUK LHD RHD vacuum Sewer Jetting Truck High Pressure Jet Suction Truck

Specifications :

| | |
|-------------------|---------------------------------|
| Place of Origin | Suizhou, China |
| Payment Terms | 30%TT |
| Supply Ability | 500unit Per Month |
| Packaging Details | Naked Packing, RO-RO, Bulk Ship |

Detail Introduction :

[Product Specification](#)

| Chassis parameters | | | |
|----------------------------------|--|--|--|
| Condition | New condition /4x2, right hand driving or left hand driving | | |
| Main details | Brand | | - |
| | Curb weight(kg) | | 8900 kg |
| | Wheelbase(mm) | | 4800 mm |
| | Dimensions(mm) | | 9120*2500*3550mm |
| | Approach/Departure angle(°) | | 20/17 ° |
| | Max. driving speed(km/h) | | 95 km/h |
| | Clutch | | Reinforced diaphragm clutch |
| | Brakes | | Air brakes |
| | Steering Gear | | Power steering, hydraulic steering with power assistance |
| | Tire | | Quantity |
| Specifications | | | 11R22.5 |
| Transmission | Manual type, FAST Brand, 8 Forwards and 1 reverse | | |
| Cabin | FOTON AUMARK Model, with Air Condition , for 2~3 persons | | |
| Engine | Brand | | Cummins Engine |
| | Horsepower(HP) | | 210 HP |
| | Fuel type | | Diesel |
| | Displacement(ml) | | 6500 ml |
| | Emission standard | | Euro 2 or Euro 3 |
| Power Supply | PTO,one is for high pressure water pump and another is for spare | | |
| Sewage Suction & Cleaning System | | | |
| Water tank | Capacity(cbm) | | 4.0cbm/4,000 liters |
| | Tank material | | Q235 carbon steel |

| | | |
|--------------------------|--|--------------------------------|
| Thickness | ? | 5 |
| Safety protection device | 1-High water level; 2-Low water level 3-No water | |
| Sewage tank | Capacity(cbm/liters) | 8.0cbm/8,000 liters |
| | Tank material | Q235 carbon steel |
| | Thickness(mm) | ? |
| | Opening of Rear Cover | 100% open by hydraulic control |
| | Working pressure | 93% Vacuum |
| | Sewer Discharging outlet(mm) | 100~150 |
| | Tank is front tipping under function of oil cylinder | |
| Sewage pump | Brand | Italian Brand Jurop |
| | Max. Working Speed(r/min) | 3300 |
| | Max vacuum | 93% |
| | Rate flow rate | 2400 L/min |
| High pressure water pump | Brand | China famous brand |
| | Type | Triple plunger pump |
| | Max. Pressure(Bar/Mpa) | ?180/18.0 |
| | Rate speed(rpm) | 1500 |
| | Rate flow(L/min) | 300 |
| High pressure Winch | Length of High pressure hose(m) | ?60 |
| | Diameters of High pressure hose(mm) | ?19 |
| Water nozzle | 10 different size water nozzle for cleaning sand,sludge and dirt | |
| Lamp | 1-Revolving Warning Light on top 2-Upper Arrow Warning light at truck rear 3-Signal light at truck rear | |
| Main parts | 1. Hydraulic controlled suction hose 2. Water-gas separator; 3. Oil-gas separator 4. Four way valve; 5. Safety valve 6. Anti overflow valve 7. Anti overflow warning device 8. Hydraulic control rear cover; 8. Tipping sewage tank body | |
| Remarks | The color is optional | |

[Reference Photos](#)





